

Assignment 3: Aircraft Performance Calculations

Solution

Instructor: Trani

Problem 1

A new airline is evaluating two aircraft to operate flights from Washington, Reagan Airport (DCA) to two important southern destinations. The following table shows the aircraft proposed by airline executives to operate from DCA. The critical stage lengths the airline would like to fly with the selected aircraft are: a) DCA-DFW and b) DCA-MIA.

Table 1. Aircraft Considered in the Airline Evaluation.

Aircraft Considered
Boeing 737-8 Max with CFM LEAP-1B28 engines. Aircraft maximum design takeoff weight is 181,000 lb. 162 seats in a two-class layout.
Boeing 737-800 (with winglets) powered by two <i>CFM56-7B24/-7B26/-7B27 engines at 26,000 LB SLST</i>). Aircraft maximum design takeoff weight is 174,200 lb. The aircraft has 160 seats in a two-class layout.

The design airport temperature used should be the average of the daily high temperatures of the hottest month of the year. More detailed information about the airport can be found at the AIRNAV database available on the web at: <http://www.airnav.com/airports/> or visit the airport site.

In your analysis use the latest version of the Boeing documents for airport design (http://128.173.204.63/courses/cee5614/sites_ce_5614.html#Aircraft_Data).

- a) Find the average stage length to be flown between each one of the critical OD airport pairs. In your analysis use the Great Circle Flight Path mapper link provided in our interesting web sites. Add 6% to the distances calculated to account for real Air Traffic route conditions and to account for possible weather deviations from the optimal Great Circle flight path.

Critical route is DCA-DFW with ~1100 nm distance (including 6% detour factor).

- b) Find the runway length needed for each one of the aircraft operating the critical route. Determine if DCA has enough runway length to support these flights.

For Boeing 737-8Max

ISA + 15 deg. C design conditions (for Boeing charts)

OEW = 98,500 lb (from payload -range diagram)

PYL = (160 passengers) (220 lb/passenger) = 35,200 lb

OEW + PYL = 133,700 lb

DTW (DCA-DFW) ~ 150,920 lb

FW ~ 17,220 lb

Runway gradient ~ 0%

Takeoff runway ~ 5,100 feet

For Boeing 737-800

ISA + 15 deg. C design conditions

OEW = 91,300 lb (from Boeing data)

PYL = (162 passengers) (220 lb/passenger) = 35,640 lb
OEW + PYL = 126,940 lb
DTW (DCA-DFW) ~ 147,180 lb
FW ~ 20,240 lb
Runway gradient ~ 0%
Takeoff runway ~ 5,700 feet

The longest runway at DCA is 7169 feet long. Both aircraft can operate from DCA with good margins.

- c) Estimate the average fuel per passenger assuming a load factor of 0.83 (83% of the seats used) for both routes. Can the airline achieve good fuel savings using the new Boeing 737-8 Max compared to the standard Boeing 737-800?

This requires that you recompute the takeoff mass with 83% of the passenger load. Otherwise the problem is similar to parts (a-b). Note that at maximum capacity, the Boeing 737-8Max burns 107.6 lb per passenger in the DCA-DFW route. The Boeing 737-800 uses 124.94 lb per passenger.

- d) Using the Payload-Range diagram of each aircraft, and using the longest flight of the two routes, find the Specific Air Range (SAR) parameter for each aircraft. Comment on the SAR values calculated.
- e) Considering various factors which aircraft is the best for this airline? Explain.

Boeing 737-8 Max seems to be the better aircraft for this operation.

Problem 2

Use the data for the transport aircraft similar to the Boeing 737-800 (http://128.173.204.63/courses/cee5614/cee5614_pub/Boeing737800Jet_class.m) to answer the following questions.

- a) Calculate total drag produced by the 76,000 kilogram aircraft during a climb profile with an Indicated Airspeed of 250 knots at 3000 meters. Assume atmospheric conditions to be ISA.
- At 3,000 meters and 250. This is equivalent to Mach 0.436 and 278 knots true airspeed.
CI = 0.6382, Cd = 0.0354, Drag = 41410 Newtons
- b) Repeat the process when the aircraft is climbing at 9,000 meters and an indicated airspeed of 280 knots
- c) At 9,000 meters and 280. This is equivalent to Mach 0.6648 and 392 knots true airspeed.
CI = 0.6275, Cd = 0.0349, Drag = 41407 Newtons
- d) Estimate the fuel consumption for each flight condition given in parts (a) and (b).
- Need to estimate the thrust generated in climb
At 9,000 meters and 280. This is equivalent to Mach 0.6648 and 392 knots true airspeed.
Thrust per engine = 60,579 Newtons
Fuel burn = TSFC * Thrust = 11.5 Newtons/second per engine (23 Newtons/second total)
- e) Find the Lift-to-drag ratio (L/D) for the aircraft while in cruise at 9,000 meters and 300 knots indicated airspeed. Repeat the calculation for the same altitude but different IAS values (250, 275, and 320 knots). Plot and comment on what would be the optimum speed to achieve the highest L/D ratio

At 9,000 meters and 300 knots indicated airspeed. This is equivalent to Mach 0.7094 and 418 knots true airspeed.

$$C_l = 0.5512, C_d = 0.0309$$

At 300 knots and 9,000 meters, $L/D \sim 17.81$

d) Find the optimal ($L/D * M$) value (M here is the true mach number) for this aircraft cruising at 9,000 meters. This factor $L/D * M$ drives the condition for maximum range for a turbofan engine aircraft.

The optimal operating point seems to be Mach 0.78 (see plot below).




Figure 1. L/D Ratio for $h=9000$ meters, Mass = 75000 kilograms, and Different Mach Numbers.

Problem 3

Use the data for the transport aircraft similar to the Boeing 737-800 and answer the following:

- Using hand or computer-aided calculations find the rate of climb for three points in the climb profile: a) 3,000 feet and 250 knots IAS, b) 10,000 feet and 280 knots IAS, and c) 25,000 feet and 300 knots IAS. Assume maximum continuous thrust in climb. Assume the aircraft mass is 78,000 kg. at all three points for comparative purposes.

b) Using the Matlab code called UnrestrictedClimbAnalysis.m provided in class, find the time to climb to 9,000 meters departing from an airport located at sea level conditions. Assume maximum continuous thrust is used and that the pilot selects a constant IAS climb profile with 280 knots IAS until reaching the cruise altitude. Assume the aircraft departs the airport at a desired takeoff mass of 76,000 kg.




Figure 2. Climb Profile. 285 IAS, 76,000 kg.

c) What is the great circle distance traveled by the aircraft to reach the Top of Climb point (TOC).

Distance to reach 30,000 feet. Takes 92.13 kilometers to climb to 9,000 meters.

Problem 4

a) An airline is evaluating operations out of El Dorado International Airport in Bogota, Colombia (airport elevation is 2548 meters above mean sea level conditions). The airline is evaluating the Boeing 787-8 and its sibling, the Boeing 787-9 to fly from Bogota to various European countries including Madrid (MAD). The typical stage length to fly to Europe from Bogota is 4,600 nm (accounting for ATC diversions). In this analysis consider the runway length available at el Dorado (use the link provided in our web page to the World Airport data). Assume ISA+15 deg. C conditions from Bogota (BOG). The airline is considering a dual class Boeing 787 configuration.

For the aircraft in question investigate the following:

a) Can the aircraft operate the route BOG-MAD (Madrid) with a full passenger load? State the numbers to justify your answer.

Boeing 787-8

DTW ~ 430,000

ISA + 15 deg. C

Runway length ~ 14,800 feet (only 12,467 available)

No, the Boeing 787-8 and the Boeing 787-9 are restricted by weight in the 4,600 nm route. The departure airport is very high.

b) Can the aircraft operate the route BOG-JFK (New York) with a full passenger load?

Yes, the BGO-JFK route can be operated with both aircraft without restrictions.

c) Find the maximum freight capacity for the BOG-JFK route above with full passenger load. State all your assumptions.

Around 38,000 lb for the Boeing 787-8 and 48,000 lb for the Boeing 787-9.

d) What version of the Boeing 787 is best suited for this airline? Explain.

Boeing 787-9.